



ZPMV2.E80735 Wiring, Printed - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

CAMPTECH II CIRCUITS INC

E80735

81 Bentley St

Markham, On L3R 3L1 CANADA

Type	Cond Width		Cond	SS/ DS/	Max	Max		Flame	Meets UL796	C	
	Min	Edge			Area	Solder	Oper				
	mm(in)	mm(in)	Thk	DSO	Diam	Limits	Temp	Class	DSR	T	
Mass laminated (multilayered) printed wiring boards, flammability only Recognition.											
ML 12-0	0.10 (0.004)	0.31 (0.012)	17 (0.67)	DS	50.8 (2.0)	280	20	130	V-0	All	*
Multi layer printed wiring boards.											
ML1	0.18 (0.007)	0.53 (0.021)	17 (0.67) Int:68.58	DS	38.1 (1.5)	288	20	130	-	▲	-
ML1-0	0.18 (0.007)	0.53 (0.021)	17 (0.67) Int:68.58	DS	38.1 (1.5)	288	20	130	V-0	▲	-
ML2	0.18 (0.007)	0.53 (0.021)	17 (0.67) Int:68.58	DS	38.1 (1.5)	274	15	130	-	▲	-
ML2-0	0.18 (0.007)	0.53 (0.021)	17 (0.67) Int:68.58	DS	38.1 (1.5)	274	15	130	V-0	▲	-
ML3	0.18 (0.007)	0.53 (0.021)	17 (0.67) Int:68.58	DS	38.1 (1.5)	288	20	105	-	All	-
ML3-0	0.18 (0.007)	0.53 (0.021)	17 (0.67) Int:68.58	DS	38.1 (1.5)	288	20	105	V-0	All	-
Multilayer printed wiring boards.											
ML 21-0	0.075 (0.003)	0.10 (0.004)	18 (0.71) Int:140	DS	50.8 (2.0)	270	10	130	V-0	All	-
Single layer metal base printed wiring board, flame only recognition.											
ML 31-0	-	-	-	SS	-	260	10	-	V-0	-	-
Single layer printed wiring boards.											
1	0.3 (0.012)	0.91 (0.036)	17 (0.67)	DS	38.1 (1.5)	288	20	130	-	▲	-
1-0	0.3 (0.012)	0.91 (0.036)	17 (0.67)	DS	38.1 (1.5)	288	20	130	V-0	▲	-
2	0.3 (0.012)	0.91 (0.036)	17 (0.67)	DS	38.1 (1.5)	260	20	105	-	▲	-
2-0	0.3 (0.012)	0.91 (0.036)	17 (0.67)	DS	38.1 (1.5)	260	20	105	V-0	▲	-
4	0.3 (0.012)	0.91 (0.036)	17 (0.67)	DS	38.1 (1.5)	288	15	130	-	▲	-
4-0	0.3 (0.012)	0.91 (0.036)	17 (0.67)	DS	38.1 (1.5)	288	15	130	V-0	▲	-
ML 11-0	0.10 (0.004)	0.31 (0.012)	17 (0.67)	DS	50.8 (2.0)	280	20	130	V-0	All	3
ML 14-0	0.10 (0.004)	0.31 (0.012)	17 (0.67)	DS	50.8 (2.0)	280	20	130	V-0	All	3
ML 41-0	0.075 (0.003)	0.10 (0.004)	18 (0.71)	DS	50.8 (2.0)	270	10	130	V-0	▲	-

* - CTI PLC is marked on individual board.



Marking: Company name or trademark or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2013-11-27

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".